





TA Plus Tile Adhesive

TA Plus is a high-performance powder-form Tile adhesive for ordinary ceramic tiles. It can be used in congested interior and exterior spaces on walls or the floor. To prepare TA Plus, mix it with water at an optimal ratio to make an efficient mixture.



Technical Data:

Temp	5-25°C
Thickness	2-5 mm
Water/powder ratio	7.5 litter of water for 25 kg of powder
Workability Time	180 min
Grouting Time	24 hours for walls and 48 hours for floors
Packaging	25 kg
Quantity per Unit Area (m ²)	2.5 kg for 4-mm notch 3.7 kg for 3.5-mm notch 4.9 kg for 8-mm notch
Initial Tensile Bond Strength	≤0.5 N/mm ²
Max. storage duration	12 months under standard conditions
Color	Gray, White





Advantages

- Easy use
- Applicable to various surfaces, including AAC blocks, concrete walls, plastered surfaces, concrete floors, and plasterboards (using a suitable primer)
- Reducing the dead load of the building
- Increasing the usable space of the building
- Fast tiling

How to Use

- Do not add water to the hardening mixture
- Do not add anything (lime, sand, cement, or plaster) to the prepared mixture
- Apply the mixture on the surface using a notched trowel (compatible with the tile size)
- Apply the mixture on the back of the tile when tiling exterior surfaces



Technical support Dept:
Call Center: (+98) 21 43000809
www.kplus.ir

GERMAN 
Technology