

Note on English translation:

This is a translation of the technical data sheet valid in Iran.

All stated details and properties are in compliance with the regulations of the Iran standards and building regulations. They are only applicable for the specified products, system components, application rules, and construction details in connection with the specifications of the respective certificates and approvals. Kplus denies any liability for applications outside of Iran as this requires changes acc. to the respective national standards and building regulations.



Technical Data Sheet

2025-2026

MASTIK

Thin coat finishing plaster

Product description

Hand applied gypsum finishing plaster for interior applications.

Storage

The bags should be stored horizontally on a flat surface such as a wooden pallet and kept dry so that they do not come into contact with water. Partly opened and / or damaged bags should not be used. Product shelf time is 6 months.

Standard referred to

ISIRI 12015-1 and EN 13279-1 category B4/50/2, the product is subject to initial type testing and continuous factory production control.

Field of application

Hand applied gypsum plaster as a final coat of surface finish for interior applications. It is used to obtain a smooth and even surface before the application of wall finishing such as paint and wall paper. If the thickness over than 1 mm is needed, it should be applied as several layers.

Application

Application

- Clean the surface and repair if necessary.
- Pour the plaster into the water in a clean container according to the appropriate mixture ratio until it exceeds the water surface for one finger. After waiting for 2-3 minutes, mix at low speed with a mechanical mixer until achieving a good mixture.
- Do not add water and gypsum to the pulped mortar.
- On the surface covered with gypsum-based plaster, proper priming should be used.

Application tools

Trowel, putty knife, etc.

Application Temperature

Do not apply below °5+C ambient, material and / or floor temperature. Fresh mortar should be protected against frost and quick drying.

Application time

- Approx. 4hr. (variable in different condition)

Properties and added value

- Smooth surfaces for fine finishing
- Easy and fast application
- High adherence quality
- Extended application duration
- A1 class material (non combustible)

Safety Instructions

- Wash hands with plenty of water after handling.
- Use protective gloves / protective clothing / eye protection / face protection.
- In case of contact with eyes: Rinse your eyes cautiously with water for several minutes. If there is a lens remove it and continue to rinse.
- If eye irritation persists: Get medical advice / attention.

Technical specifications

Description	Unit	Value
Color	-	White
Reaction to fire	-	A1
Compressive strength	N/mm ²	≥ 2.0
Flexural strength	N/mm ²	≥ 1.0
Adhesive strength	N/mm ²	≥ 1.0
Initial setting time	minute	380-500
Final setting time	minute	400-520
Amount of mixing water (for 10 kg dry plaster)	L	6-7
Application temperature	°C	5 to 40
Shelf life	month	6

Packaging

Product	Weight (kg)	Packaging (pcs./pallet)	Material Number
MASTIK	20	60	7013332000

It is suggested to follow the technical details which given on Kplus system brochures for application.

Kplus Direct: Technical Support Dept.

- ▶ Phone: (+98 21) 88207929
- ▶ Fax : (+98 21) 88203126
- ▶ technical@kplus.ir

All technical changes reserved. Only the current printed instructions are valid. Our warranty is expressly limited to our products in flawless condition. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas. The stated information represents current state-of-the-art Kplus technology. The entire state of approved engineering rules, appropriate standards, guidelines, and rules of craftsmanship are not included herewith. These and all application instructions have to be adhered to separately by the installer.

All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require the express permission of Kplus.

Head Office:

No. 19, East Qobadian Alley, Nelson Mandela (Africa) Blvd., 19176-34611, Tehran, Iran